



nonwoven fusible
INTERLININGS

The soul of the Garment



www.sbttextiles.com | raipur@sbttextiles.com

Product Range

Fabric: Thermal Bond Nonwoven

GSM: 20 to 120

Width: 40", 44", 60", 80", 88"

Fiber Blend:

- Virgin Polyester
- GRS Certified Recycled Polyester
- Nylon
- Viscose

UV and UV Free

Coating:

- PES
- HDPE
- PA (Machine Wash & Enzyme Wash)

UV and UV Free

Colour: White, Black & Charcoal

100% Polyester PES Coated

- UV and UV Free

Article	Weight (g/m ²)
211 DD	23
251 DD	25
301 DD	30
351 DD	35
401 DD	40
451 DD	45
501 DD	50
551 DD	55
601 DD	60
651 DD	65
801 DD	80
901 DD	90

100% Polyester PA Coated

- 40°, 60° & 90° Machine Wash
- Enzyme Wash

Article	Weight (g/m ²)
211 DD PA	23
251 DD PA	25
301 DD PA	30
351 DD PA	35
401 DD PA	40
451 DD PA	45
501 DD PA	50
551 DD PA	55
601 DD PA	60
651 DD PA	65
801 DD PA	80
901 DD PA	90

50% Polyester 50 % Nylon PA Coated

- 40°, 60° & 90° Machine Wash
- Enzyme Wash

Article	Weight (g/m ²)
211 NY DD PA	23
251 NY DD PA	25
301 NY DD PA	30
351 NY DD PA	35
401 NY DD PA	40
651 NY DD PA	65

SBT Textiles Pvt. Ltd.

Unit 1: 589, Urla Industrial Area
Raipur, Chhattisgarh, India
Pincode: 493221

Unit 2: Plot No 619 and 612 B,
Urla Industrial Area,
Raipur, Chhattisgarh, India
Pincode: 493221

Unit 3: Solar Power Plant,
Chandanu, Dist. Bemetara,
Chhattisgarh, India
Pincode: 491335

Contact: +91 70009 77174

Email: raipur@sbttextiles.com

Website: www.sbttextiles.com